

# Combinações

## MH070FXEA4B

Unid. Exterior	Combinação de unidades interiores						Capacidade de arrefecimento (W)					Capacidade			Consumo de Energia			Corrente			EER	Grau	COP	Grau
	A	B	C	D	%	Total	A	B	C	D	Total	Min. W	Nom. W	Max. W	Min. W	Nom. W	Max. W	Min. A	Nom. A	Max. A				
1 Unid.	2000	-	-	-	29%	2000	2400	0	0	0	2400	1350	2400	3000	380	780	950	1.7	3.6	4.3	3.08	B	2.63	E
	2600	-	-	-	37%	2600	2600	0	0	0	2600	1350	2600	3480	390	840	1100	1.8	3.8	5	3.10	B	2.64	E
	3500	-	-	-	50%	3500	3500	0	0	0	3500	1350	3500	4200	400	1130	1580	1.8	5.2	7.2	3.10	B	3.04	D
	5200	-	-	-	74%	5200	5200	0	0	0	5200	1400	5200	6240	420	1520	2160	1.9	7	9.9	3.42	A	3.35	C
2 Unid.	2000	2000	-	-	57%	4000	2000	2000	0	0	4000	1500	4000	4800	410	1240	1490	1.9	5.7	6.8	3.23	A	3.61	A
	2000	2600	-	-	66%	4600	2000	2600	0	0	4600	1690	4600	5520	420	1430	1720	1.9	6.5	7.9	3.22	A	3.62	A
	2000	3500	-	-	79%	5500	2000	3500	0	0	5500	1770	5500	6600	430	1710	2050	2	7.8	9.4	3.22	A	3.41	B
	2000	5200	-	-	103%	7200	1940	5060	0	0	7000	1900	7000	8400	580	2180	2520	2.7	10	11.5	3.21	A	3.63	A
	2600	2600	-	-	74%	5200	2600	2600	0	0	5200	1750	5200	6240	420	1660	2000	1.9	7.6	9.2	3.13	B	3.63	A
	2600	3500	-	-	87%	6100	2600	3500	0	0	6100	1820	6100	7320	440	1880	2260	2	8.6	10.3	3.24	A	3.45	B
	2600	5200	-	-	111%	7800	2330	4670	0	0	7000	1900	7000	8400	580	2130	2540	2.7	9.7	11.6	3.29	A	3.62	A
	3500	3500	-	-	100%	7000	3500	3500	0	0	7000	1900	7000	8400	580	2120	2530	2.7	9.7	11.6	3.30	A	3.62	A
	3500	5200	-	-	124%	8700	2820	4180	0	0	7000	1900	7000	8900	580	2110	2540	2.7	9.7	11.6	3.32	A	3.61	A
5200	5200	-	-	149%	10400	3500	3500	0	0	7000	1900	7000	8900	580	2000	2540	2.7	9.2	11.6	3.50	A	3.78	A	
3 Unid.	2000	2000	2000	-	86%	6000	2000	2000	2000	0	6000	1810	6000	7200	440	1800	2280	2	8.2	10.4	3.33	A	3.61	A
	2000	2000	2600	-	94%	6600	2000	2000	2600	0	6600	1870	6600	7920	440	1830	2460	2	8.4	11.3	3.61	A	3.88	A
	2000	2000	3500	-	107%	7500	1780	1780	3120	0	6680	1900	6680	8020	580	1835	2410	2.7	8.4	11	3.64	A	4.25	A
	2000	2000	5200	-	131%	9200	1520	1520	3960	0	7000	1900	7000	8900	580	1850	2460	2.7	8.5	11.3	3.78	A	4.39	A
	2000	2600	2600	-	103%	7200	1850	2400	2400	0	6650	1900	6650	7980	580	1830	2410	2.7	8.4	11	3.63	A	4.21	A
	2000	2600	3500	-	116%	8100	1670	2160	2910	0	6740	1900	6740	8080	580	1840	2460	2.7	8.4	11.3	3.66	A	4.28	A
	2000	2600	5200	-	140%	9800	1430	1860	3710	0	7000	1900	7000	8900	580	1880	2460	2.7	8.6	11.3	3.72	A	4.37	A
	2000	3500	3500	-	129%	9000	1520	2650	2650	0	6820	1900	6820	8180	580	1850	2510	2.7	8.5	11.5	3.69	A	4.28	A
	2000	3500	5200	-	153%	10700	1310	2290	3400	0	7000	1900	7000	8900	580	1930	2510	2.7	8.8	11.5	3.63	A	4.30	A
	2600	2600	2600	-	111%	7800	2240	2240	2240	0	6720	1900	6720	8050	580	1840	2420	2.7	8.4	11.1	3.65	A	4.27	A
	2600	2600	3500	-	124%	8700	2030	2030	2730	0	6790	1900	6790	8150	580	1850	2460	2.7	8.5	11.3	3.67	A	4.27	A
	2600	2600	5200	-	149%	10400	1750	1750	3500	0	7000	1900	7000	8900	580	1880	2510	2.7	8.6	11.5	3.72	A	4.34	A
	2600	3500	3500	-	137%	9600	1900	2550	2550	0	7000	1900	7000	8900	580	1880	2460	2.7	8.6	11.3	3.72	A	4.34	A
3500	3500	3500	-	150%	10500	2330	2330	2330	0	6990	1900	6990	8900	580	1900	2510	2.7	8.7	11.5	3.68	A	4.30	A	
4 Unid.	2000	2000	2000	2000	114%	8000	1680	1680	1680	1680	6720	1900	6720	8070	580	1850	2460	2.7	8.5	11.3	3.63	A	4.27	A
	2000	2000	2000	2600	123%	8600	1580	1580	1580	2040	6780	1900	6780	8140	580	1880	2460	2.7	8.6	11.3	3.61	A	4.27	A
	2000	2000	2000	3500	136%	9500	1470	1470	1470	2590	7000	1900	7000	8900	580	1900	2460	2.7	8.7	11.3	3.68	A	4.30	A
	2000	2000	2600	2600	131%	9200	1520	1520	1980	1980	7000	1900	7000	8900	580	1880	2460	2.7	8.6	11.3	3.72	A	4.37	A
	2000	2000	2600	3500	144%	10100	1390	1390	1800	2420	7000	1900	7000	8900	580	1900	2510	2.7	8.7	11.5	3.68	A	4.30	A
	2000	2600	2600	2600	140%	9800	1420	1860	1860	1860	7000	1900	7000	8900	580	1900	2460	2.7	8.7	11.3	3.68	A	4.30	A
	2000	2600	2600	3500	153%	10700	1310	1700	1700	2290	7000	1900	7000	8900	580	1930	2550	2.7	8.8	11.7	3.63	A	4.30	A
	2600	2600	2600	2600	149%	10400	1750	1750	1750	1750	7000	1900	7000	8900	580	1900	2550	2.7	8.7	11.7	3.68	A	4.30	A