

Desempenho do sistema
System performance
Performance du système

Marcação CE - Resultados previstos

CE Marking - Predicted results

Marquage CE - Résultats prévu

NP EN 14351-1

Janela 2 folhas com 1.60x1.40m

Vidro : 66.1 + 14 + 6 + 14 + 44.1

2 leaves window 1.60 x 1.40m

Glass: 66.1 + 14 + 6 + 14 + 44.1

Fenêtre 2 vantaux 1.60m x 1.40m

Verre: 66.1 + 14 + 6 + 14 + 44.1

Permeabilidade ao AR

AIR Permeability

Perméabilité à l'AIR

4

Estanquidade à ÁGUA

WATER Tightness

Étanchéité à l'EAU

E900

Resistência ao VENTO

WIND Resistance

Résistance au VENT

C5

Coef. Transm. TÉRMICA

THERMAL Transmittance

Coef. de Transmission THERMIQUE

Uw = 0,89 W/m² K

Ug = 0,6W/m² K (Janela 2 folhas com 1,60x1,40m)

Ug = 0,6W/m²K (2 leaves window with 1,60x1,40m)

Ug = 0,6W/m²K (Fenêtre de 2 vantaux avec 1,60x1,40m)

Rw janela(dB)= 48dB

Rw (IGU) = 51dB, área ≤ 2,70m²

Rw (IGU) = 51dB, area ≤ 2,70m²

Rw (IGU)=51dB, aire ≤ 2,70m²

Isolamento ACÚSTICO

ACOUSTIC Insulation

Isolation ACOUSTIQUE

